Panasonic ideas for life

KX-TS580EX1/EX2 KX-TS560EX1/EX2 KX-TS520EX1/EX2

- Caller ID Compatible†*1
- Phonebook (50 Entries)*1
- Ringer Indicator

*1 Except KX-TS520EX1 / EX2.



Caller ID



Ringer Indicator







Speakerphone

A Simple, Easy-to-Use Design to Match Every Need



KX-TS580EX1 / EX2





KX-TS560EX1 / EX2





KX-TS520EX1 / EX2







KX-TS580EX1 / EX2 KX-TS560EX1 / EX2 KX-TS520EX1 / EX2 Integrated Telephone System

The KX-TS580EX1/ EX2 and KX-TS560EX1/ EX2 Equipped

with Handy Features, Including Both LCD Display and Caller ID



RoHS-specified
No Chemical Used substances
Lead, cadmium, mercury, hexavalent chromium and
specified brominated flame retardants (PBB and PBDE)



Outstanding Features with Built-In Quality

Caller ID Compatible

The KX-TS580EX1 / EX2 and KX-TS560EX1 / EX2 are suitable for Caller ID service. The 2-Line LCD

displays caller's name (required registration in phonebook) and number.

You can know who's calling before you answer.

Phonebook (50 Entries)

Up to 50 numbers and names can be stored in its phonebook. You can make a call by selecting a name or number from the phonebook.

Except KX-TS520EX1 / EX2.

Ringer Indicator

You can confirm incoming calls visually. Ringer Indicator flashes to indicate there is an incoming call.

Convenient when waiting for a call.

| pecifications | | RA-18500EA2 | |
|-------------------------------|--|--|-----------------------|
| | Black | Black | Black White |
| | | | |
| Number of Line | 1 | 1 | 1 |
| Data Port | • | • | • |
| One Touch Dial | _ | _ | 3 |
| Redial Memory | 20-Station | 20-Station | Last One |
| Auto Redial | • | _ | _ |
| One Touch Redial | • (Last One) | • (Last One) | • (Last One) |
| Phonebook Name Input | English (50 Entries) | English (50 Entries) | _ |
| Pulse / Tone Default | Tone Fix | Tone Fix | Tone Fix |
| Flash Time | Programmable | Programmable | 100 ms Fix |
| Flash Time Default | 100 ms | 100 ms | |
| Insertable Pause | 3.5 s | 3.5 s | 2.1 s |
| Ringer Volume | Off / Low / High | Off / Low / High | Off / Low / High |
| | On / Low / Ingh | • Tright | • • |
| Ringer Indicator | · · | · | • |
| Electronic Hold | • | _ | _ |
| Electronic Hold on Music | • | _ | _ |
| Speakerphone | • | _ | _ |
| Speakerphone Volume | 8-Step | _ | _ |
| Mute | • | • | _ |
| On-Hook Dialing | • | • | _ |
| Handset Receiver Volume | 4-Step | 4-Step | 6-Step |
| Call Restriction | Programmable (0 or Up to 2 digits) | Programmable (0 or Up to 2 digits) | _ |
| Dial Lock | • | • | _ |
| Navigator | • | • | — |
| | | | |
| LCD | Dot x 16 digits 7-Seg x 8 digits + Pict | Dot x 16 digits 7-Seg x 8 digits + Pict | _ |
| LCD Language (Menu Selection) | English / Spanish / Italian / Greek / Turkish / German | English / Spanish / Italian / Greek / Turkish / German | _ |
| LCD Language Default | English | English | _ |
| LCD Contrast | 4-Step | 4-Step | _ |
| r ID | | | |
| Caller ID Compatible | • | • | _ |
| Signal | FSK&DTMF | FSK&DTMF | _ |
| Private Name Display | (Required Registration in Phonebook) | (Required Registration in Phonebook) | _ |
| Caller ID Memory | 50-Station | 50-Station | <u> </u> |
| Time / Day Stamp from Clock | 50-Station | 50-Station | _ |
| Time / Day Stamp Hom Clock | • | • | |
| Power Source | 3 x AA and Line | 3 x AA and Line | Line |
| Wall Mountable | 3 X AA and Line | 3 X AA and Line | Line |
| | | 106 100 05 | |
| Dimensions W x D x H (mm) | 196 x 190 x 95 685 | 196 x 190 x 95 665 | 196 x 190 x 95 518 |

